


HEATsat Stops Snow Outages

Back-side electric heater keeps snow & ice from forming on the dish, by heating the reflector when snow and ice HEATsat starts @ \$4K



Parts to fix old Sat Dish

Call for help choosing replacement

parts such as

feedhorns.

Page 2





New improved "1dB compress" specs help for HD sat reception



CLNB20-PL05L \$319 Page 8

Satellite Products

Satellite "Dish" Antennas **Heaters & Covers**



3340 S Lapeer Rd, Orion, MI 48359 • P 248-391-9200 • F 248-391-9207

Visit DAWNco booth #SU6813 • NAB show • Las Vegas, April 11-14, 2011

PRSRT STD **US** Postage PAID **DAWNco**

\$439

actuator

ACT3600-REED



"Call your DAWNco Technical Sales representative, for competitive prices and help choosing the best product for your needs"



D15-W-NPRM @ \$349 ask for DAWNco **BROADBAND**

with Small Dish

1.5 meter sat antenna

with integrated non-

penetrating mount

Products Catalog See multi-channel delivery equipment, such as: encoders, decoders, antennas & modulators.



ask for DAWNco **FIBER OPTIC Products Catalog**

See TX & RX units to pass a/v, cableTV, satellite and data.

3.7 meter HIGH GAIN satellite dish


Simple 1-axis polar mount to scan entire arc of satellites. 1-piece spun aluminum reflector for best surface accuracy & high gain. Fits on 5.5"OD pipe. Purchase separately the controller, actuator, feedhorn, LNBs, and cement pad.

stationary #D37F \$2278 motorized #D37P \$2379



SATELLITE FIBERLINK for long distance cable run starting @ \$1K per TX/RX link

Don't put up with signal outages caused by long coaxial cable runs. Install a satellite fiberlink to eliminate loss problems, plus provide lightning protection.



Receiver / Decoder for MPEG4-MPEG2-420 and DVB S2

This unit is loaded with all of the features you need for HiDef, and your company's budget bosses will appreciate the price. backward compatibility for SD. The PV7 has SAT L band input. Output a/v, ASI, SDI, HDSDI

PV7MP24S2-SH420-Sat SD & HD Sat Receiver

\$3199 see page 7

See policies at DAWNco web site. Prices & product details subject to change at any time, without notice.

Over 1000 items at sat 1 www.DAWNco.com Pictures & Spec's

call DAWNco 800-866-6969 248-391-9200



..and Reception Improving Products **HD Grade LNBs • TI Filters**



Reasonable prices, priceless reasoning.

1.8m Ku Band Network Dish

site network. Stationary satellite antenna, with built-in non-penetrating roof mount. Strong 1-piece reflector. Purchase separately the feed & LNBs.

Economical design is perfect for multi-

1.8m Offset CALL

ALUMINUM 1-piece Satellite Antennas

Easy Install • Economical

GOOD 1-axis MOTORIZED using 1 actuator

Simple 1-axis polar mount to scan entire arc of satellites. 1pc spun aluminum reflector for best surface accuracy & high gain. Fits on 5.5"OD pipe. PuchSep: controller, 1-ActArm, feed, LNBs, pad.

3.7 meter #D37P \$2379 most popular size, Gain: 42.3dB @ 4Ghz, 51.5dB @ 12Ghz.

4.2 meter #D42P \$4191 highest gain pipe-mounted dish, Gain: 43.5dB @ 4Ghz, 53.0dB @ 12Ghz.

Option: 4pc easy-ship reflector

BETTER 2-axis MOTORIZED using 2 actuators

Perfect peaking with actuator arm based dual axis drive. Commercial grade sat antenna, 1pc reflector for easy install. Fits on 5.5"OD pipe. PuchSep: controller, 1-ActArm, feed, LNBs, pad.

3.7 meter #D37P-MD \$3369 most popular size, Gain: 42.3dB @ 4Ghz, 51.5dB @ 12Ghz.

4.2 meter #D42P-MD \$5198 highest gain pipemounted dish, Gain: 43.5dB @ 4Ghz, 53.0dB @ 12Ghz.

+NPRM Ku gain 45.5dB @ 12Ghz. NPRM Ku Gain 45dB @ 12Ghz. Heavy-Duty 5.0 meter stationary • 1pc dish

 Easy install 1-piece spun-aluminum reflector always installs perfectly, and always produces

high gain (unlike competing multi-panel dishes that don't always get installed properly).

 Massive 16" diameter steel king post for good

reception in high winds C band gain is 44.5dB,

Ku band gain is 54.2dB

Option for factory install

PuchSep: Feed, LNBs & Cement pad



#D18-W- 1.8m PrimeFocus \$466

Heavy-duty motorized system with massive steel "D-drive," mounts on a single 5.5" OD pipe. 2-axis horizon-to-horizon mount for perfect

peaking on entire arc of sats, plus low sats on east & west.

popular size, Gain: 42.3dB @ 4Ghz, 51.5dB @ 12Ghz.

mounted dish, Gain: 43.5dB @ 4Ghz, 53.0dB @ 12Ghz.

3.7 meter #D37MHHP-MD \$5899 most

BEST dual-axis MOTORIZED horizon-to-horizon

COVERsat

Prevent signal outages from snow

"CoverSat Keeps Snow Off Dish"

Satellite antenna cover, made to exactly fit the customers specified dish type, custom fit to antenna dimensions specified by customer. Reduce signal outages due to "winter" weather. When wrapped over the front face of a

dish, the cover creates a steep slippery surface to prevent accumulation of ice & snow. Attenuation=less than .3 dB

\$179 For Small Dish Cover 1.2m size #CS1.2x1.4

\$499 Cover for 3.7 meter dish

\$799 Cover for 4.5 meter dish

Call DAWNC

Totally stop ice & snow buildup with **HEATsat**

Prevent signal outages with Electric HEATING system for satellite antenna, customer installed on FULL back side of dish. Kit includes: specialized heat tape sized to form a grid on the dish backside, sensors for precipitation and temp, electric power junction box, wiring harness, and installation instructions. Customer must provide proper power.

\$3999 For 3.0m Dish #HEATsat-3.0full

\$4999 For 3.7m Dish #HEATsat-3.7full



\$6499 For 4.5m Dish #HEATsat-4.5full

Over 1000 items at

www.DAWNco.com

Pictures & Spec's

ULTIMATE dual-axis MOTORIZED "Gibralter" Highest gain dish with massive "Gibralter" 2-axis az/el motorized mount, utilizing jumbo "crane-like" pivot point. Precise movement to any sat, with perfect peaking. PuchSep: controller, feed, LNBs, pad.

4.2 meter #D42MHHP-MD \$7319 highest gain pipe-

4.5 meter #D45MAE \$9533 most popular size, Gain: 43.9dB @ 4Ghz, 53.3dB @ 12Ghz.

5.0 meter #D50MAE \$10,198 highest gain dish, Gain: 44.5dB @ 4Ghz, 54.2dB @ 12Ghz.

3.7m stationary

Good commercial grade sat antenna in most popular size. 1-piece for easy install. Mount onto 5.5" OD pipe.

\$2278 fixed #DH37FAE

sat 2

2.7m fixed or motorized PLB


Gain: 39.6dB @ 4Ghz, 49.2dB @ 12Ghz. Use included PLB lock-bar for fixed, act-arm for motorized Gain: 40.6dB @ 4Ghz, 49.9dB @ 12Ghz. Use included PLB lock-bar for fixed, act-arm for motorized

DH30PLB-48 \$1008

2.4m fixed or motorized PLB

Gain: 38.6dB @ 4Ghz, 48.2dB @ 12Ghz. Use included PLB lock-bar for









Reasonable prices, priceless reasoning.

FIBERGLASS Multi-Panel Satellite Antennas

Easy Ship • Roof Mountable

2.4 meter offset C or Ku UPLINK

4-piece SMC fiberglass reflector, az/el mount, TX gain: 42.0 dB @ 6Ghz, 49.2 dB @ 14Ghz. Mount on customer provided 6.62"OD pipe. Reflector accuracy suitable for RX & TX applications. OPTIONS: heater, non-penetrating roof mount

stationary 2.4m intelsat approved \$1899

stationary 2.4m C receive/transmit Ku receive/transmit intelsat approved

motorized AZel 2.4m with Tracking controller for inclined orbit sats \$10,999 #P24MAEOrt & CONTROLLER \$2166 #P24FOSrt-K-IA*



3.8 meter offset UPLINK & downlink

4 piece SMC fiberglass reflector, az/el mount, TX gain: 46.5 dB @ 6Ghz, 53.0 dB @ 14Ghz. Includes kingpost to mount on cement pad. Reflector accuracy good for RX & TX applications. OPTIONS: C band version, heater, non-penetrating roof mount

receive/transmit \$11,333 #P38FOSrt*

receive/transmit \$17.999 #P38FOSrt-HEATED*

w-Tracking controller w-Controller & interface

FIBERGLASS Small Ku Band SAT Antennas Stationary • Low Wind Load

1.8 meter Offset DOWNLINK

1 piece SMC fiberglass reflector, az/el mount, choose 1 or 2 port Ku offset feedhorn. Ku band gain = 45.5 dBi. Mount onto customer provided 4.0 inch OD pipe.

stationary 1.8 Dish stationary 1.8 Dish & HEATER #P18FOS \$499 **#P18FOS-HEATED \$1499**

CHOOSE Ku 2-port feed & struts ONE #P18FOS-ADD-2KI CALL Ku 1-port feed & struts #P18FOS-ADD-1KI CALL

OPTION: Non-penetrating roof mount #P18FOS-ADD-NPRM CALL

2.4 meter prime focus DOWNLINK

3 piece SMC fiberglass reflector, az/el mount, choose or 2 port Ku feedhorn. Gain: 37.5 dB @ 4Ghz, 47.0dB @ 12Ghz. Mount onto customer provided 5.5 inch OD pipe. Option: C band feedhorn.

stationary 2.4 Dish stationary 2.4 Dish & HEATER #P24F-HEATED CALL #P24F \$799

CHOOSE Ku 2-port feed & struts #P24F-ADD-2KI \$200 Ku 1-port feed & struts #P24F-ADD-1KI \$200

OPTION: Non-penetrating roof mount #P24F-ADD-NPRM CALL




FAST SHIP 1.0 meter dish

FedEx shippable, 1 piece SMC fiberglass reflector, az/el mount, choose 1 or 2 port Ku offset feedhorn. Ku band gain = 40.5 dBi. Mount onto 1.9" OD pipe. Purchase separately: LNBs, pipe mount.

stationary 1.0m pipe mounted hold LNBF CALL 2 port Ku \$219 #P10FOS-LNBF #P10FOS-2K

2 port Ku CALL #P10FOS-NPRM-2K



3.7 meter fixed or motorized

Perfect dish for rooftop or island location, where 8 petal design offers easy transport to site. Mount on 6.625" OD pipe extending 6ft above surface, holds Chap or SEA feedhorn. C band gain = 40.9 dBi / Ku band gain = 50.7 dBi. Feedhorn, LNB and pipe sold separately.

stationary 3.7 Dish

motorized 3.7 Dish

\$1899 #P37F

Super Value

#P37P \$1999

3.0m Aluminum 1-axis Motorized

1-piece aluminum dish, motorized polar mount, HD 36 inch actuator & motor, RC1500 position controller, 2 port C/ku motorized feedhorn, good C & Ku LNBs, RG11 signal cable, motor wire, and power supply for LNBs.

SATPACK-D30P 54K

1-piece aluminum dish, motorized polar mount,

HD 36 inch actuator & motor, RC1500 position

C & Ku LNBs, RG11 signal cable, motor wire,

SATPACK-D37P 55K

5.0m Aluminum 2-axis Motorized

Heavy-duty aluminum dish, motorized AZ/EL "Gibralter" mount, RC2000 position controller, 2

port C/ku motorized feed, best C & Ku LNBs, RG11 signal cable, motor wire & splitter/power

and power supply for LNBs.

controller, 2 port C/ku motorized feedhorn, better

Motorized Satellite DISH PACKAGES

(includes all items except: pad, freight, installation)



Antenna



Controller

3.7m Aluminum 1-axis Motorized

supply for LNBs. SATPACK-D50MAE \$14K



www.DAWNco.com

sat 3

4.5m AZ/EL stationary

3.0m fixed or motorized

Mount on 6.625" OD pipe. C

gain = 49.0 dBi. Feedhorn,

band gain = 40.0 dBi / Ku band

LNB and pipe sold separately.

stationary 3.0, #P30F \$1299

motorized 3.0, #P30P \$1599

High gain dish in 24 panel design for easy transport to site. Holds Chap or SEA feedhorn. C band gain = 42.9 dBi / Ku band gain = 52.6 dBi.

#P45F CALL

3.4m fixed or motorized

has feed support to hold Chap or SEA feedhorn. C band gain = 40.2 dBi / Ku band gain = 49.8 dBi.

stationary 3.4, #P34F \$1699 motorized 3.4, #P34P \$1799

"Ask us about discounts for ordering LARGE **QUANTITIES** of any item"


and Complete Sat Antenna Packages

Dish, Feed, LNBs, Controller



call DAWNco 800-866-6969 248-391-9200





Feedhorn Retrofit & Fiberlink

C & ku band feedhorn parts

Fixed 4-port C&Ku band feed for reception of all channels on

a C/Ku band satellite. 4port GOOD \$349 FEED-4CK-ECON

4port BEST \$1198 FEED-4CK-HQ



Fixed 2-port C band feed for reception of all channels on a C band satellite.

2port GOOD \$79 FEED-2C

2port BEST \$499 FEED-2C-HQ

STATIONARY 4-port C/Ku Feedhorn MOTORIZED 4port C/Ku Feedhorn

For reception of all channels on any C/Ku band satellite. Motor rotates entire feed, w-POT

sensor. \$2399 FEED-4CK-MOTHQ-POT

MOTORIZED 2port C/Ku Feed

Reception of 1 polarization C band and 1 polar-

ization Ku band. Pulse motor adjusts C&K polarization.

\$139 FEED-2CK-MOT

Fiberlink for SMALL dish Perfect signals over long distances Secure Path for Military & FEMA

High Gain 1.0 meter offset dish

With offset feed strut to hold LNBF. 1-piece fiberglass reflector.

#P10FOS-LNBF \$249

DirecTV LNBF with two F ports

Integrated feed & LNB, place at front of dish to amplify DirecTV signals #KLNBFD1.0-G3K \$39

2-Polarization STACKER

Places even polarity channels above odd, on 1 RF 950-2150 Mhz out #MS-STACKER-US575T \$199

Satellite L band FIBERLINK

Convert RF channels from LNBF, into fiber optic signal, for long distance cable

Transmitter #FSS-95F12T \$799 Receiver #FSS-95F12R \$589

System for DirecTV 2-feed service

(101 satellite, odd & even channels)

Fiber

SingleMode

2-Polarization UN-STACKER

One RF input, unstacks odd & even channel bands, to 2 RF outputs

#MS-UNSTACKER-D575D \$219

Muliswitch routes signals to Recrs

Box that collects signals from dish, and routes into sat receivers

for up to 6 feeds #MS68AMP CALL

DirecTV 5-feed offset dish

Elliptical dish with multi-port LNBF, for reception of all SD & HD DirecTV channels

#DTV.8FOS-plusSL5 CALL

LNBF Locker for 5 polarizations

Box provides appropriate DC current to each LNBF F connector, 13/18 vdc & tone

4 feed #MS-LOCKER-4SATPL CALL 5 feed #MS-LOCKER-5SATPL CALL

System for DirecTV

5-feed service

Stationary Ku offset feed

Feedhorn for stationary offset Ku band satellite antenna. Customer verify attachment

> 1-port Ku \$89 **FEED-1KOF**



2-port Ku \$119 FEED-2KOF

Put NEW feed on OLD dish

RETROFIT-KIT will replace the existing feedhorn and struts, to support a new C or Ku band focal point of



the dish.

KIT4-8MBF-CLAMP

C band 90° elbow for C band feed. Flanges are smooth-to-groove.



90C-E \$175 "E" easy bend



90C-H \$268 "H" hard bend

Ku band 90° elbow for Ku band feed. Flanges are smooth-to-groove.





90KU-E \$49 "E" easy bend 90KU-H \$288 "H" hard bend

C Band LNA "old style"

LNA mounts at feehorn, amplifies 3.7-4.2 Ghz sat signal, output on N connector (no block down conversion)



sat 4


Replacement HQ feed motor

Replacement kit for high quality motorized feedhorns. Unit includes: Motor and



Over 1000 items at

www.DAWNco.com



Coax

Cable

SPECIAL PRICES until July 31,'11 while QTYs last



call DAWNco 800-866-6969 248-391-9200





Reasonable prices, priceless reasoning.

Signal path from Satellite LNB

Low Loss Cable • Amps Satellite **Fiberlinks**

5C Cable for motorized dish


Five (5) conductor cable used to connect outdoor satellite dish to indoor controller, provides these separate cables under one black PVC jacket: 2 conductor/16gu, PLUS 3 conductor/18gu, with foil shield & drain, and overall black UV resistant PVC jacket. 500ft reel



99¢ per foot 5C1618S

15C Cable for motorized dish

Fifteen (15) conductor cable for 2-motor satellite antenna, to link outdoor satellite antenna motors & sensors with indoor controller. Consisting of 15 conductors with 4 individually jacketed groups cabled together and jacketed overall. 500ft reel. Call for details.



In-Line Amplifier for LNB signal Amplifier for +20dB gain on LNB cable

run, pass 950- 2150 Mhz signals, preset slope, 4dB noise

\$20



L Band Attenuator Pads

Use when signal hitting receiver is too high. Choose value (3,6,10, or 16 dB).Order in 10-packs

power pass \$7ea DAT-*-P

power block \$7ea DAT-*-NP



with outdoor rated TRANSMITTER

Starting at \$1788 per LNB



Satellite Fiberlink

"Use fiber when Dish-to-Receiver

"no need for heated shack near dish"



Distance is over 300ft'

- · Good for dish-to-receiver distances OVER 300ft, so you can place Satellite Antennas anywhere you want.
- · High signal levels reach control room, to feed many Sat Receivers
- Increase EbNo readings on "finicky" digital sat receivers
- Outdoor rated TX can be placed in box on back of dish, for use in hot or cold climates (operation from -40 to +158 degrees F)
- Optional items: fiber cable, enclosures, power supply, chassis & patchcords.



for Sat Fiberlink, mount temp-stable TX on dish \$1199 #FSS-95F5T

FIBER CABLE, 800ft easy-pull to dish, factory connectorized with protective Pulling Eye

VISA




Outdoor rated TRANSMITTER Wall mount RECEIVER locate RX inside at far end of fiber run, in air conditioned location \$589 #FSS-95F12R



locate RX inside rackmounted chassis CALL #FSS-95F5R (chassis PurchSep)





call DAWNco 800-866-6969 248-391-9200

Over 1000 items at

www.DAWNco.com

Pictures & Spec's

"Eliminate Cable loss Problems" LOW-LOSS Satellite SIGNAL CABLE



60% braid prevents interference, 0.4 inch OD for easy installation

RG11F-SAT 71¢ft



DAWNflex for distances up to 500ft Quad-shielded to prevent interference ingress, and integrated lightning protection with proper connector

DAWNflex.6QF @ \$1.29 foot

Use low-loss coax cable made specifically for SATELLITE "L" BAND frequencies, sweep tested to 3 Ghz, flooded for direct burial. New "DAWNflex.6QF" can cut signal path loss in half, compared to other common coax cable types. Available in 500ft or 1000ft reels. See loss comparisons for satellite signals on coax cable for 100ft at 1450 Mhz: DAWNflex.6QF = 3.12 dB, RG11 = 5.39 dB, RG6 = 7.49 dB.

RG11 Crimp tool

This is the proper tool for good RG11 connections. Crimp tool with 2 hex sizes: .475 & .324 & pin

CT611 \$79

F connector for DAWNflex.6QF "F" type connectors with integrated lightning protection ground lugs DF.6QF-compress-F \$32 each

Cable stripper tool for RG11 & RG6 **UDT59611-Deluxe \$79**



Cable stripper tool for DAWNflex.6QF #DF.6QF-stripper \$89

F connector for RG11F-sat

\$3.50 each GF11AHS460

UPLINK: Ku Band BUC

transmitter that up-converts block of signals & amplifies for uplink to satellite. IN: 950-1450 MHz on 'F' connector, OUT: 14.0-14.5 GHz to WR75 flange that attaches to separate feedhorn.

4 Watt Ku

8 Watt Ku CALL TXKU8.0F

CALL for the BEST PRICE on the power level you need



Dish mounted

of signals & amplifies for uplink to satellite, IN: 950-1525 MHz 'N' connector 50 Ohm, OUT: 5.850-6.425 Ghz to CRP 137G flange that attaches to separate feedhorn.

5 Watt C CALL

10 Watt C **CALL** TXC10N

CALL for the BEST PRICE on the power level you need



Block Downconverter C to L

UPLINK: C Band BUC

3.7-4.2 GHz input on 50 Ohm 'N' connector, ¶ converted to 950-1450 MHz output on 75 OHm 'F' connector. High

sat 5

CALL BD37N-95F-**PL10** stability ±10 Khz stability

Block Downconverter Ku to L converts 11.70-12.75

Ghz to 950-2000 MHz. input on 50 OHm 'SMA' connector, output on 75 OHm 'F' connector, LO stability +/- 12 KHz



Block Converters

Tell us what you need, and we will find it

SPECIAL PRICES until July 31,'11 while QTYs last

Controllers & Signal Splitters

Actuators • Mounts **Power Supplies**

Controller for DUAL axis motorized dish

Rack mounted unit provides simple and reliable interface, for



controlling motorized sat antenna that has 2-motor drive system. Controls feedhorn polarization adjustment. 50 sat positions. Option: PC control software

\$2649 CONTROL-2000A

& 24vdc feed drive & wire to motors. PC Remote Software \$699

Controller for SINGLE axis motorized dish

Most popular rackmounted controller, for controlling motorized sat dish



Get the best "Thomson

most important moving

ACT2400-REED

Non-Penetrating ROOF mount

part on your sat dish

Saginaw" actuator, for this

24 inch ACTUATOR & motor

that has 1-motor drive system. Also controls feedhorn polarization. 50 preset positions. Option: PC control software and 24vdc feed drive.

sh. CALL NPRM-PXL2

36 inch ACTUATOR & motor

Super strong & reliable. The best "Thomson Saginaw" brand of heavy-duty actuator arm, with 36vdc motor

\$439 ACT3600-REED

BaseStand holds dish on pad

An "X" shaped steel base supports 5.5 inch OD top pipe, which holds dish on cement pad \$520 DBASESTAND



Holds 3.8m sat dish on roof. 4

trays & 5.5"OD top pipe. Call for unit to hold your dish.

OPTION: Parking lot mount to avoid zoning delays

PC CONTROL of satellite dishes that utilize RC2000 controller

remote dish control \$699 RCSOFT-REMOTE

Satellite receiver control CALL

Software allows a remote user access to all control modes on a satellite dish controller (RC2000 type only). A remote user can send front panel keystrokes to the controller and view the controller's 2x40 Liquid Crystal Display. One copy of the software can work with multiple

RC20001s. A text file specifies the controller1s address.

call DAWNco 800-866-6969 248-391-9200

Over 1000 items at www.DAWNco.com

Pictures & Spec's

sat 6

"DivinSup" AMPLIFIED SPLITTER

1 LNB can feed up to 16 Receivers • Zero thru loss

Two 1x5 amplified \$239 splitters, DIVINSUP-2-1x5A

One 1x16 amplified \$339 splitters, DIVINSUP-1x16AE



Boost signal level coming from dishmounted LNBs. Unit holds amplified signal splitters,

so each LNB can feed many sat receivers. Each unit includes one 1000ma power supply, to power two LNBs with 18vdc.

Passive Splitters for Satellite Feed

8-way \$36 DED778A

4-way \$25 DED774A

6x8 Input Selector for SAT receivers

MultiSwitch functions as a 6x8 Matrix when used with sat receivers that can back-feed 13 or 18 DC through RF-input port, selecting proper A or B sat feed input (no 22 Khz tone needed). PurchSep: #DCP7A for continuous 18 vdc power to LNBs. MS68-AMP \$149

Power Supply for LNBs

Inserter module provides power to two LNBs, with external 1000ma wall-mount power supply. Select-switch for 18vdc for two LNBs, or 18/13vdc for LNBF

Power 2 LNBs w/1amp PowSup #DCP7A-1000 \$79



bower

Power Supply for LNBs

Power 28+ LNBs with redundant 10 Amp. power supplies in rack mount. Output 18Vdc@10A via 16 pair of fused (0.7A time-delay) output connections.

Redundant 10amp PowSup #QRPS18x24-10B \$2450

Voltage Block for LNB signal run

Voltage blocking coupler blocks DC current in coaxial cable, passes 5 to 2150 MHz with .3 dB insertion loss, F male to F female

(buy in 5 packs) рувс \$6 еа

Patch Panel for SAT feeds

route L-band (950-1450Mhz) signals from antenna mounted LNBs to receivers. Rack mount unit has INPUT row of 24 patch ports, above OUTPUT row of 24 patch ports. Simple plug-in patch cords are used to route signals from input to desired output. Speicfy "Normal" or



Straight" configuration when ordering. "Patchcord" SFPP2424-2ftCord \$18

See policies at DAWNco web site. Prices & product details subject to change at any time, without notice.



Reasonable prices, priceless reasoning.

Testing & Monitoring Spectrum Analyzer Constellation Viewer



PV7MP24S2-SH420-Sat SD & HD Sat Receiver



#PV7MP24-SH420-IP @ \$3549

HD & SD Receiver / Decoder for MPEG4-420 & MPEG2-420

This unit is loaded with all of the features you need for HiDef, and your company's budget bosses will appreciate the price. The PV7 is a receiver and decoder for both SATELLITE L band input (with available configuration for IP input). Receive HiDef, plus backward compatibility to standard-def. Demodulate and decode MPEG4-420 and MPEG2-420, with compatibility for DVB-S2/S. Outputs are baseband A/V and ASI, plus SDI connector which will support HD or SD mode. The unit has the ability to cross convert utilizing a built-in format converter, and analog output is available together simultaneously with SDI output. Your audio needs are covered with embedded 8 channel audio, and Dolby AC3. Unit can be controlled with web browser, and has full SNMP (10/100 ethernet) monitor/control support.

MPEG2 "SD" Satellite Receiver

Use this digital receiver to tune most standard definition MPEG2 422 & 420 sat channels, that are transmitter in the clear. Input sat L band. Output baseband a/v, and SDI with embedded audio.

Ethernet remote control on Scopus unit.

SIRD2980 \$2399



DigiCipher Satellite Receiver

DSR4550 supports digital component video (SDI) with 2 channels of embedded audio, ASI input/output and Gig-E output

"Best" DSR4550 CALL

"Econ" DSR4410X CALL

Compass & Inclinometer

Indicate compass heading

steps, adjustable něck band

SAT-MASTER

& elevation in 5 degree

for front-of-face visual sighting of object while

reading meter displays.

Digital Meter for peaking dish

Bar-graph indicates power level for sat. Provides 18vdc power to LNB. Includes case, power cord, & rechargeable



Use to establish level, and set elevation on sat dish. Hands free mode with "beep" indication.



tion. \$149 SMARTLEVEL

Digital SmartLevel & 24" rail

\$209

SmartLevel module installed in 24" rail. Display shows: degrees, percent slope, & pitch.



SMARTLEVEL-24RAIL \$199

call DAWNco 800-866-6969 248-391-9200

www.DAWNco.com

Pictures & Spec's

Over 1000 items at

sat 7

RACK & CARRY Spectrum Analyzer

Unique rack-mounted spectrum analyzer has internet remote-view for regular performance monitoring from any PC. Push quick-release on rack mount and quickly stuff unit into the included padded carrying case, for temporary portable usage at dish site. Frequency coverage from up to 2150 Mhz in 4 bands. No display screen. Use ethernet port for remote monitoring via internet or other IP connection. Includes LABVIEW software for PC at remote site to view all functions on Spectrum Analyzer. Comparison of satellite carrier levels, with adjustments for band, span, and reference level.

SA2150B1C \$3399 Satellite L band for 950-2150 Mhz

> SA2500C \$3899 Cable & OffAir & Sat band for



Rack Mounted 16x1 INPUT SELECTOR

Place in front of spectrum analyzer. Remote monitor all your RF feeds, all of the time. Remote



SFS16X1-WithSoftware \$999 control software included.

Satellite Identifier & dish peaking tool

\$719 BESTbuddy29



Portable and rugged Satellite Signal Level Meter to measure 950 -2150MHz satellite L band signals. Unit powers the LNB, and provides digital signal measurement for carriers. The unit can identify satellites by name (based on units ability to auto-compare actual measurements, to ID tables which the user will periodically download to the unit). Measures satellite signal levels, -70 to -10 dBm, with carrier-to-noise (C/N), signal quality (IRD Equivalent value), BER (Bit Error Rate). The user can confidently recognize the satellite the antenna is aimed at, with the positive ID feature or use of the automatic scan mode, to identify

the unknown satellite.

Survey Horn & LNA combó

Use in front of spectrum analyzer, when troubleshooting source for TI interference.

SURVEYHORN-LNA-combo



Tools for Satellite
Compass • Inclinometer
Level • Spectrum Analyzer



Reasonable prices, priceless reasoning.

Satellite Products

HD Grade LNBs • TI Filters Satellite "Dish" Antennas

C band LNB • Economical ±250 Khz

DRO type LNB, for reception of analog sat channels. Best reception specs for an economical non-PLL type LNB.



C band LNB **BEST - HD Grade**

New generation of C band LNB has improved "1dB compression" & "phase noise" specs that make a real difference in the reception of HD sat channels. Boost your digital receiver EbNo readings! Low 250ma power draw.

\$249

20° ±5 Khz CALL CLNB20-PL05L



20° ±25 Khz

CLNB20-PL25L

Ku band LNB **BEST - HD Grade**

The "skinnier housing" isn't the only thing improved on this new TOP-END Ku band LNB. Improved "1dB compression" and "phase noise" specs can make a real difference in the

reception of HD sat channels. Best unit for MPEG4 / 8PSK reception. Upgrading your LNB is a fast & easy way to improve your digital receiver EbNo readings! Low 250ma power draw won't overtax your receiver power supply.

New .6 dB ±5 Khz CALL KLNB.6-PL05L

> .7dB ±15 Khz \$249 KLNB.7-PL15L

Ku band LNB • Economical ±500 Khz

High Stability DRO type LNB, for reception of analog sat channels. Best reception specs for an economical non-PLL type LNB.



KLNB.7-D500 \$119

Ku LNB • Switch for High-Low bands

For worldwide use with any Ku satellite, has external selector switch to select input. Choose LOW band 10.70-11.70 GHz, or choose HIGH band input 11.70-12.75 GHz. Stability rating +/- 25 Khz.



sat 8

KLNB.7-PL25-SWITCH2 CALL

call DAWNco 800-866-6969 248-391-9200

Over 1000 items at

www.DAWNco.com

Pictures & Spec's

DAWNco

3340 S Lapeer Rd, Orion, MI 48359 P 248-391-9200 • F 248-391-9207 Email: Sales@DAWNco.com Web: www.DAWNco.com

TI "Interference" Filter **Blocks Radar from** Airports & Military

C band TI filters installed between feedhorn & LNB. Airport & marine radar frequently wipe out Sat-Dish

reception located close to the radar. Sites near military bases & flight paths are also effected. The TI filters suppress strong out-of-band interference

from radar. C-BANDPASS-6LIGHT \$339

TI Filter for SAT + WiMax protection

Like above, but with additional band-edge attenuation to stop SAT interference from new WiFi data paths. C-BANDPASS-7WiMax CAL

Filter passes 11.7 to 12.2 Ghz Ku band frequencies, and rejects all others.

Ku-BANDPASS CALL



DAWNflex boosts ___ signal levels see page 5

Fix many reception problems by simply replacing the cable! DAWNflex improves signal quality, and can cut signal path loss in half, on signal cable run from dish to building. Flooded for direct burial. Quad-shielded to prevent interference ingress.

#DAWNflex.6QF \$1.29 per FT

Lightning Surge Suppressor

Don't let lightning strikes near dish damage equipment at the other end of cable run.



"Stop knuckle busting during LNB installation"



C-HARDWARE-DELUX \$38

Deluxe Stainless LNB bolt set

Used when attaching C band LNB to feedhorn. Stainless steel allen head bolts with narrow profile for limited-spacefor-bolts installations. Includes (18) bolts-nuts-washers.

"Call your DAWNco **Technical Sales**

representative, for competitive prices and help choosing the best product for your needs"



See policies at DAWNco web site. Prices & product details subject to change at any time, without notice.